

REVOLUTIONIZE YOUR END-OF-LINE [PACKAGING] PERFORMANCE



Fully Automatic
Strapping Machine



Corrugated Cardboard



SoniXs Sealing Unit | Standard-6



electrical drives




For PP-Straps and Banding foil (option)



6-sided electro-mechanical package alignment (option)









FULLY AUTOMATIC CORRUGATED CARDBOARD STRAPPING MACHINE

The UCB efficiently straps complex 4- and 6-point folding cartons. An optional six-sided electromechanical alignment system ensures an optimal package position for strapping. Effortless replacement of the strapping unit allows for easy switching between straps of different widths.

A special feature of the UCB is the combination of strapping and banding in one machine: both variants are possible in the same UCB aligning station with a quick and easy changeover.

TECHNICAL DATA

Performance: Up to 32 single strappings per minute Up to 20 double strappings per minute; with two package stops and a conveyor speed of 1.0 m/sec Conveying Height: 800 - 1.000 mm on castors 970 - 1,150 mm (option)

Straps:

PP straps: Width: 5 - 12 mm Thickness: 0.4 - 0.63 mm

Strap Coil Dispenser: Core diameter: 200 mm Core width: 190 mm

Electricity:

Voltage: 100 - 240 V, 50 / 60 Hz, 1L+N+PE

(others on request)

Power consumption: approx. 0.6kW

Weight: (without options) 1,250 mm → 1,600 ka $1,650 \, \text{mm} \rightarrow 2,000 \, \text{kg}$

Format Sizes**: [in mm]

	Length	Width	Height	:
Package min.	150	105	20	
Package max.	1,400	1,200 / 1,600	400	

^{**}without package alignment backside

Second package stop for second strapping

STANDARD FEATURES


SoniXs Utrasonic sealing unit in standard-6 version High availability due to controlled frame -----5-sided electromechanical package alignment -----Continuously adjustable conveyor speed Laterally driven transport belts ______ Driven top belts Electro-mechanical package stop and hold-down device Intuitive user guidance via colored touch panel with ergonomic positioning options _____ ATR - Automatic cycle rate regulation Easy maintenance due to automatic removable strapping unit ______


Automatic machine adaptation to package dimen-

_____ CE marking inclusive conformity declaration

sions via adjustable recipes

DIMENSIONS / WORKING WIDTH MACHINE (in mm)





OPTIONS

Fully automatic strap coil change by double strap Low strap detection with signal in the control panel -----Infeed table incl. package stop Three-part signal light (LED) -----Banding unit (technical data can vary) Package alignment backside ______

HOLISTIC SUPPORT WITH THE MOSCA SYSTEM

Suitable consumables available directly from Mosca. Can be combined with Mosca maintenance contracts - all from one source.

CONTACT US FOR A PERFORMANCE CONSULTATION!

mosca.com

Mosca GmbH

Gerd-Mosca-Straße 1 · 69429 Waldbrunn

info@mosca.com · +49 6274 / 932-0